



Waterproof Quick Connector IP68

- Housing: Nylon + PC
- Conductor: Brass
- Rated Power: CONN005: 24A 450VAC; CONN006-007: 32A 450VAC
- Rated connecting capacity: CONN005: 0.5-2.5mm²; CONN006-007: 0.5-4.0mm²
- CONN005 available cable diameter (Rubber): 8-11mm
- CONN006-007 available cable diameter(Rubber): 4-8mm /8-12mm
- CONN005 Extra 8-11mm Rubbers included in the packet
- CONN006-007 Extra 8-12mm Rubbers included in the packet
- Refer to stripping length: External stripping 25mm; Internal stripping 7mm

IP68 Rated	1 YEAR Replacement Warranty
----------------------	--



CONN005



CONN006



CONN007

Accessories

Product Breakdown

CONN005 Dimensions: Total length 94.19mm, diameter 24.96mm.

CONN006 Dimensions: Total length 97.1mm, diameter 94.38mm, terminal diameter 71.88mm, terminal spacing 32.56mm.

CONN007 Dimensions: Total length 139.71mm, diameter 139.71mm, terminal diameter 30.00mm, terminal spacing 54.20mm.

Components: Sealing Ring, Main Body, Screw Cap, Tightening Ring, Terminal.

Part No.	Description	Max. Current	IP Rating	Box Size (cm)	Box Weight (kg)	Carton Qty
CONN005	CONNECTOR / 2 Way Cable Extension Quick Connect IP68 W/PROOF BLK 24A 450VAC	24A	IP68	15x15x3	0.1	1/125
CONN006	CONNECTOR / 3 Way T Shape Cable Extension 3Pin Terminal IP68 W/PROOF 32A 450VAC	32A	IP68	18x14x4	0.1	1/125
CONN007	CONNECTOR / 3 Way Y Shape Cable Extension 3Pin Terminal IP68 W/PROOF 32A 450VAC	32A	IP68	18x14x4	0.1	1/125