

sales@clalighting.co.nz

Tel: +64 9 427 6133 | Fax: +64 9 427 6134



WIG SERIES

Exterior LED Surface Mounted Featured Up/Down Wall Lights



Product Features:

- Exterior Surface mounted up/down LED wall lights
- Input voltage: 100-240V AC 50/60Hz
- Driver output voltage: 18-42V
- Driver input current: 0.053A
- Driver output current: 300mA
- Inrush current: 1.2A
- Housing: powder coated aluminium
- Bracket: PC
- LED chip: 2pcs 5050
- Power factor: >0.5
- 2 stickers included which allow narrowing of beam angle at both or either end
- Beam angle: without sticker is 69.9° and with the sticker is 32.7°
- Ambient Temp: -20 to 50°C
- Suitable for 2-way switching
- Suitable for use with PIR or Microwave sensors











Part No.	WIG1
Colour	Powder coated dark grey UP/DOWN
Kelvin	3000K
Lumens	550lm
Watt	11W
Weight	0.85kg
Вох	21x12x8cm
Carton QTY	1/8



Part No.	WIG2
Colour	Powder coated white UP/DOWN
Kelvin	3000K
Lumens	550lm
Watt	11W
Weight	0.85kg
Box	21x12x8cm
Carton QTY	1/8



Back plate